










RESIDUAL-CURRENT DEVICE COMPON.SUMMATION
CURR.TRANSF. W/O PICK-UP DELAY WINDOW 40MM
RTD.FAULT CURRENT 0.3A

General technical details:		
Item designation / according to DIN 40719 extendable after IEC 204-2 / according to IEC 750		K
Item designation / according to DIN EN 61346-2		K
Ambient temperature		
• during operating	°C	-20 ... 70 ...
Mechanical design:		
Diameter / of the feedthrough	mm	40
Conductor cross section that can be connected / of the terminal	mm ²	2.5
Width	mm	100
Height	mm	65
Depth	mm	85
Certificates/approvals:		

General Product Approval			Test Certificates	
 CSA	 GOST	 UL	Special Test Certificate	
Shipping Approval			other	
 DNV	 GL	 LRS	 RMRS	Declaration of Conformity other
Further information:				
Information- and Downloadcenter (Catalogs, Brochures,...) http://www.siemens.com/industrial-controls/catalogs				
Industry Mall (Online ordering system) http://www.siemens.com/industrial-controls/mall				
CAX-Online-Generator http://www.siemens.com/cax				
Service&Support (Manuals, Certificates, Characteristics, FAQs,...) http://support.automation.siemens.com/WW/view/en/3UL2201-1A/all				
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...) http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3UL2201-1A				

last change:

Jan 21, 2013